


# Replacement for SMJD-3V16W4PD-XX


Seoul Semiconductor
L. CN MD Development 2.
2021.06.29


### 1. Appearance and Dimension (Old vs New)

#### As is SMJD-3V16W4PD-XX



#### To be **SMJA-3G16C30C-XX02**





< 2 >

## 2. Optical value and Function (Old vs New)

Index	Unit	SMJD-3V16W4PD-XX	SMJA-3G16C30C-XX02	Remark
IC Tyep	-	Acrich3.0	WD15-S30T	
IC	EA	2	1	
Circuit topology	-	4step	3step	
Input Voltage	Vrms	230VAC	230VAC	typical
Power	W	16.6	16.6	typical
PF	-	>0.9	>0.9	
THD	%	<20%	<20%	
CRI	-	>80	>80	
Flux	lm	1470	1700	typical
PLW	Lm/w	89	106	typical
Color Range	-	4 step	4 step	
Dimming	-	TRAIC	TRAIC	10~100%
Flicker	%	100	<28	Title 24
SVM	-	>3	<0.4	
ССТ	K	2700	2700	
LED type	-	SAW8C72A	SAW8A32E-E2(H)	
LED Q'ty	EA	30	30	
PCB size	mm	Ø70mm	Ø70mm	Round

< 3 >

## Legal Disclaimer

Information in this presentation is provided in connection with Seoul Semiconductor products and/or business operation. While Seoul Semiconductor has made every attempt to ensure that the information contained in this presentation has been obtained from reliable sources, Seoul Semiconductor is not responsible for any errors or omissions, or for the results obtained from the use of this information.

All information in this presentation is provided "as is" with no guarantee of completeness, accuracy, timeliness or of the results obtained from the use of this information, and without warranty of any kind, express or implied, including, but not limited to warranties of merchantability, performance, and fitness for a particular purpose, or any warranty otherwise arising out of any proposal, specification, or sample.

In no event will Seoul Semiconductor, its related corporations, or the employees thereof be liable to you or anyone else for any decision made or action taken in reliance on the information in this presentation or for any consequential, special or similar damages, even if advised of the possibility of such damages.