

Medical Power Supply

160 Watt Medical Series | Desktop Type


Features

- IEC/EN/ANSI/AAMI ES60601-1 (Edition 3.1)
- EMC : IEC60601-1-2 : 2014 (Edition 4.0)
- IEC 60950-1
- Means of Protection: 2 X MOPP
- Touch Current : < 100µA
- 100-240VAC Universal Input
- Single Output to 160W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Modified and Custom Design Available
- Green Mode
Meet CEC , DoE Level VI, Energy Star, ErP Stage 2,
No Load Power Consumption Less Than 0.21W



Model

Model	O/P Voltage	O/P Current	Watt
ATM160T- P120	12.0V	12.5A	150W
ATM160T- P190	19.0V	8.4A	160W
ATM160T- P240	24.0V	6.6A	160W
ATM160T- P480	48.0V	3.3A	160W



Input

Voltage	100-240VAC
Line Frequency	50/60Hz
Current	1.8A-0.9A
Protetction	Internal Primary Current Fuse
Configuration	IEC60320/C6,C14

ATM160T-P Series

Output

Load Regulation	±5% (Typical)
Ripple & Noise	1% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection
DC Cord	UL 2464 / UL 2095
Ferrite Core	No (Optional)

Safety Approvals

CB / UL / cUL / FCC / CE / T-mark(TÜV) / PSE
--

Electrical

Topology	LLC
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100µA
Efficiency	Meet DoE Level VI
EMC Standards	EN55011
	EN61000-3-2,3
	EN61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental

Operating Temperature	0 to +40°C
Storage Temperature	-20 to +80% RH
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Case Dimension	L 183 × W 81 × H 42 (mm)
Weight	820g (Ref.)