

I.T.E / Medical Open Frame Dual Output

210 Watt IT/Medical Series | Open Frame

Features

- IEC/ANSI/AAMI ES60601-1 (Edition 3.1)
- Means of Protection : 2 X MOPP
- Touch Current : < 100µA
- IEC 60950-1
- 100-240VAC Universal Input
- 210W With Fan
- Standby 5V / 2A
- On & Off Remote Control
- Regulated Output With Low Ripple Noise
- Modified and Custom Design Available
- Green Mode
- Meet CEC, DoE Level VI, ErP Stage 2, No Load Power Consumption Less Than 0.21W







RoHS

Model

Model	O/P Voltage	O/P Current		Watt	
		Convec-tion	With Fan*	Convec-tion	With Fan*
ATM210T- F120	12V	12.5A	16.7A	160W	210W
	5V	2.0A			
ATM210T- F240	24V	6.25A	8.3A	160W	210W
	5V	2.0A			
ATM210T- F480	48V	3.13A	4.17A	160W	210W
	5V	2.0A			

ATM210T-**FXXX**

O / P Voltage ←

Input

Voltage	100-240VAC
Line Frequency	50/60Hz
Current	2.5A-1A
Protetction	Internal Primary Current Fuse

Output

Load Regulation	±5% (Typical)
Ripple & Noise	1% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection

Safety Approvals

CB / UL / cUL / FCC / CE

Electrical

Topology	LLC
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100µA
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental

Operating Temperature	0 to +50°C
Storage Temperature	-20 to +80% RH
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	160W With convection cooling 210W With fan cooling

Mechanical

Case Dimension	L 127 × W 76 × H 38 (mm)
	5" x 3" x 1.5"
Weight	310g (Ref.)