

LED Power Supply Constant Current Driver

- Long lasting and high reliability
- Extra small compact housing
- suitable for use with downlights, Spotlights and other indoor LED applications



Approval marks



Item	Value Unit Remarks
------	------------------------

1. Input

Nominal Voltage	220 – 240 VAC
Nominal frequency	50 - 60 Hz
AC voltage range	200 – 264 VAC Permitted voltage range
DC voltage range	NA V
Maximum voltage	264 V 2hrs
Nominal current	200 mA 230V @ 42W load
Total Harmonic Distortion (THD)	< 20 % Full load, 230 V, 50 Hz
Power factor	0.95 Full load, 230 V, 50 Hz
Efficiency	>85% Full load, 230 V, 50 Hz, typical
No-load power	< 1W 230V, typical
Stand-by power	NA W
Power loss	6.3W at 230V input @ 42W load max.
Input power	48.3W at 230V input @ 42W load max.
Protection class	II
Inrush current	< 5 A twidth = 100 µs typical (measured at 50% Ipeak)

2. Output

Nominal voltage range	50 - 84 VDC
Maximum voltage	95VDC Open circuit
Nominal current range	500Ma
Current accuracy	+/- 5 %
Current ripple	10 % typical
Nominal power range	≤42 W Partial Load.
Maximum power	42 W Ta ≤ 45°C,
Safety isolation	SELV-equivalent 3,0 kVrms . Touch current < 0.7 mA

3. Environment


Ambient temperature range t_a	-20 ... +50°C
Maximum case temperature t_c	85 °C Measured on t_c point indicated of the product label
Max. Case temp. in fault condition	110 °C
Storage temperature range	-25 ... +75 °C Cool down before operating
Relative humidity	5 ... 80 % Not condensing
Surge transient protection	1 kV L/N acc. IEC 61000-3-2 (ANSI C62.41 Cat.A ...)
Environmental rating	Indoor
IP rating	IP 20
Mains switching cycles	> 100'000
Expected lifetime	30,000hrs @ t_c = 85°C, B10
	50,000hrs @ t_c = 75°C, B10

4. Protection

Overheating protection	yes, automatic reversible
Overload protection	yes, automatic reversible
Short-circuit protection	yes, automatic reversible
Hot plug-in protection	No, Hot plug-in or secondary switching of LEDs is not permitted and may cause a very high current to the LEDs.

5. Dimension, Weight


Dimensions	137*42.5*29.5mm
Weight	145g
Max. cable length	1.2m
Cable crosssection, input side	0.5...1.5 mm ²
Cable crosssection, output side	0.2...1.5 mm ²




Safety and EMC standard

Safety according to
EN 61347-1 , 61347-2-13, 62493
RI suppression according to EN 55015 /CDN
Line harmonics according to EN 61000-3-2
Immunity according to EN 61547


Variable Input Vs Efficiency



Variable Input Vs Vout Measurement



Variable Input Vs PF Measurement



Disclaimer

The information in this data sheet subject to change without notice.
Always make sure to use the most recent release, or consult with us before your final selection.