

KHATOD®

Optical Solutions for LED Lighting

Via Monfalcone, 41

20092 Cinisello Balsamo - Milan - Italy

technical@khatod.com

Tel. (+39) 02-660-136-95, Fax. (+39) 02-660-135-00

Technical Department
Product's Technical Brief



Ultra Narrow Punch Beam Lens

- LED Chip Projection on target totally eliminated;
- Clean Spot, Efficiency > 89%;
- Optical Grade PMMA;
- 3 Pins provided for precise and robust mounting;
- Available in **35 mm, 46.8 mm, and 50 mm** diameter;
- FWHM = 3.5° for 1 mm² chip area LEDs;
- CBCP (Center Beam Candle Power) = 150 cd/lm;
- Smallest Shape Factor Lens (Diameter × FWHM / ChipSize).



Illuminance values are computed for 25 W luminaire of 120 lm/W LEDs

Lens



25 m (82 ft)
720 lux

50 m (164 ft)
180 lux

75 m (246 ft)
80 lux

100 m (328 ft)
45 lux

Typical Applications

- Punch Beam;
- Spot light;
- Entertainment lighting;
- Architectural lighting;
- Wall washer;
- Stage lighting;
- Decorative lighting;
- Shop windows, halls & entrances;
- Flashlights.

Beam Angle for Common LEDs

- 3.5° CREE XLAMP XP-E2;
- 4.2° CREE XLAMP XP-E;
- 5.2° CREE XLAMP XP-G2;
- 5.5° CREE XLAMP XP-G;
- 5.5° OSRAM OSOLON SQUARE;
- ... and more on <http://www.khatod.com>.

Part Number & Dimensions

PL1672UN: $\phi = 35.0$ mm, H = 21 mm
 PL1675UN: $\phi = 50.0$ mm, H = 21 mm
 PL1738UN: $\phi = 46.8$ mm, H = 21 mm