

Specification

PUVA SENSOR

SU^{*}VISEN 400

Part No. : SPUVA-CS-S3528-A (A-Z)

Part No. : SPUVA-CS-C3535-A (A-Z)

Part No. : SPUVA-CS-T18-A (A-Z)

Seoul Viosys Co., Ltd.		
Drawn by	Checked by	Approved by


Customer		
Checked by		Approved by

SPUVA-CS-S3528

SUVISEN 400




Feature GaN Based Material
Active Area A = 0.121 mm²
SMD3528 PKG / Silicon Molding type
High UV sensitivity & Low Dark Current



Applications NUV LED Monitor

Outline Diagrams and Dimensions(3528)




Maximum Ratings

Parameter	Symbol	Value	Unit	Remark
Operating Temperature	T _{opt}	- 40 to + 85	℃	
Storage Temperature	T _{sot}	- 40 to + 85	℃	
Soldering Temperature	T _{sol}	260	℃	Within 10sec
Reverse Voltage	V _R	3	V	

General Characteristics (@ 25℃)

Parameter	Symbol	Value (typical)	Unit	Test Conditions
Active Area	A	0.121	mm ²	400 x 400 μm ²
Responsivity	R	~ 0.20	A/W	λ=355nm, Vr=0V
Dark Current	I _D	< 1	nA	Vr = 1V
Photo Current	I _{ph}	~ 200	nA	UVA Lamp, ~1mW/cm ²
Temperature Coefficient	I _{tc}	< 0.3	%/℃	UVA Lamp
Spectral Detection Range	λ	200 ~ 400	nm	Cut off : 10% of R

Spectral Responsivity (A/W)



* Wrist bands or Anti-electrostatic gloves : If possible, utilize wrist bands and Anti-electrostatic gloves.
This precautionary measure is to ward off ESD damage.


www.seoulviosys.com

SPUVA-CS-C3535

SUVISEN 400




Feature GaN Based Material
Active Area A = 0.121 mm²
SMD3535 PKG / Quartz cover type
High UV sensitivity & Low Dark Current



Applications UVA, B, C source Monitor
UV LED Monitor

Outline Diagrams and Dimensions(3535)




Maximum Ratings

Parameter	Symbol	Value	Unit	Remark
Operating Temperature	T _{opt}	- 40 to + 85	℃	
Storage Temperature	T _{sot}	- 40 to + 85	℃	
Soldering Temperature	T _{sol}	260	℃	Within 10sec
Reverse Voltage	V _R	3	V	

General Characteristics (@ 25℃)

Parameter	Symbol	Value (typical)	Unit	Test Conditions
Active Area	A	0.121	mm ²	400 x 400 μm ²
Responsivity	R	~ 0.20	A/W	λ=355nm, Vr=0V
Dark Current	I _D	< 1	nA	Vr = 1V
Photo Current	I _{ph}	~ 200	nA	UVA Lamp, ~1mW/cm ²
Temperature Coefficient	I _{tc}	< 0.3	%/℃	UVA Lamp
Spectral Detection Range	λ	200 ~ 400	nm	Cut off : 10% of R

Spectral Responsivity (A/W)



* Wrist bands or Anti-electrostatic gloves : If possible, utilize wrist bands and Anti-electrostatic gloves.
This precautionary measure is to ward off ESD damage.


www.seoulviosys.com

SPUVA-CS-T18

SUVISEN 400




- Feature**
- GaN Based Material
 - Active Area A = 0.121 mm²
 - TOPKG / BSG type
 - High UV sensitivity & Low Dark Current



- Applications**
- UVA, B, C source Monitor
 - UV LED Monitor

Outline Diagrams and Dimensions(TOPKG)



Side View

Top View

BSG : Borosilicate glass


Maximum Ratings

Parameter	Symbol	Value	Unit	Remark
Operating Temperature	T _{opt}	- 40 to + 85	℃	
Storage Temperature	T _{sot}	- 40 to + 85	℃	
Soldering Temperature	T _{sol}	260	℃	Within 10sec
Reverse Voltage	V _R	3	V	

General Characteristics (@ 25℃)

Parameter	Symbol	Value (typical)	Unit	Test Conditions
Active Area	A	0.121	mm ²	400 x 400 μm ²
Responsivity	R	~ 0.20	A/W	λ=355nm, Vr=0V
Dark Current	I _D	< 1	nA	Vr = 1V
Photo Current	I _{ph}	~ 200	nA	UVA Lamp, ~1mW/cm ²
Temperature Coefficient	I _{tc}	< 0.3	%/℃	UVA Lamp
Spectral Detection Range	λ	200 ~ 400	nm	Cut off : 10% of R

Spectral Responsivity (A/W)



* Wrist bands or Anti-electrostatic gloves : If possible, utilize wrist bands and Anti-electrostatic gloves.
 This precautionary measure is to ward off ESD damage.

www.seoulviosys.com