



# LED Power Supply

**Constant Voltage LED Driver | Input 200 – 240V AC | Output 24V DC**

High Cost Performance, SELV. short circuit, overload and over temperature protection.  
Compliance to ERP directive, lifetime 30,000hrs



items	conditions	request	note
-------	------------	---------	------

## Input

Input voltage	Ta	200-240Vac	--
Input Frequency		50Hz/60Hz	--
Input Current		<0.5A	--
Input Power	25°C, rated input voltage, output with max. rated power	<70W	--
Efficiency		≥85%	--
Standby	25°C, rated input voltage, output without load	<0.21W	Average
Inrush Current	25°C, rated input voltage	<75A	peak
PF	25°C, rated input voltage, output max. rated power	≥0.9	--

## Output

Startup time	25°C, rated input voltage, output with max. rated power	<0.5S	--
Output voltage and precision	Ta , rated input voltage, output with rated power	24V±5%	--
Output current range	Ta , rated input voltage	0-2.5A	30W
Output voltage wave	25°C, rated input voltage, output with max. rated power	150mV	Vp-p
Output overload	25°C, rated input voltage, output with 2 times LED load	yes	--
Output current and precision	Ta , rated input voltage, output with rated power	--	--
Rated output voltage range	Ta , rated input voltage,	-	--
Output current wave	25°C, rated input voltage, output with max. rated power	--	Ip-p
Dimming mode	--	--	--
Dimming range	--	--	--

## Protection

open circuit	Ta, input rated voltage, output without load	--	--
overload	Ta , 0.94-1.06 times of input voltage, 1.2 times of rated power	yes	--
Short circuit	Ta , input 0.94-1.06 times input voltage,	yes	--
Over temperature	IC detect temperature	--	--
Over voltage	Ta , 0.94-1.06 times of input voltage, output voltage is 1.5 times of rated one	yes	--
Auto recovery	Over load, short circuit revocation	yes	--
Latch off	Over voltage, over heat re-start after cut off	--	--

**Temperature and others**

Operating temperature	--	-20° C ~ 45° C	--
Relative humidity	--	45%~ 85%	--
max. Case temp.	--	90° C	--
products life span	under max Ta,input rated voltage and output max rated load	30,000hr	--
working noise	25°C, rated input voltage,output with rated power, mute box background noise<35dB, pickup 10cm distance from products	yes	--

**Mechanical, mounting**

Case material and size	Plastic case
Mounting ways	independent
Insulation type	Class II
IP grade	IP20
Input cables dimension	H03VVH2-F 2*0.75mm <sup>2</sup>
Output cables dimension	H03VVH2-F 2*0.75mm <sup>2</sup>
Output cables length	--

**Standard**

Safety	IEC61347-1 IEC61347-2-13
Harmonic	EN61000-3-2 Class C
EMC	EN55015
EMC	EN61000-4-2, -3, -4, -5, -6, EN61547

**Dimensions**