



Sensata
Technologies

TEMPERATURE SELECTION GUIDE



Elektronik GmbH

Autorisierter Distributor:

Neumüller Elektronik GmbH | Gewerbegebiet Ost 7 | D-91085 Weisendorf
Tel. +49 9135 73666-0 | info@neumueller.com | www.neumueller.com





Temperature Switches & Thermostats

Temperature Switches/Thermostats mechanically react to a system's media based on a predetermined temperature value. Depending on the product line, switches may be used as indicators or cut-offs monitoring the temperature of liquids, gases, or surfaces in a system.

1NT Series

The 1NT is a single throw snap-action, fixed temperature thermostat.

Application Opportunities

The 1NT can fit a variety of different applications and can be used as a regulating thermal switch, over-temperature control, or pilot duty control switch.

Features

- Ambient temperature range from -40°C to 240°C
- ISO9001-2000 certification
- Lower Cost
- Automatic reset, manual reset, trip free manual reset, one shot configurations available

Application Examples

- HVAC
- Power Supplies
- Automation
- Medical equipment

Agency Approval

- UL/CSA recognized
- ENEC/ENEC recognized



3NT Series

The 3NT is an automatic reset thermostat built in an easy to mount package that allows for operation in moist environments.

Application Opportunities

The 3NT's easy mount clip makes it ideal for remote location within applications. Its innovative dry seal makes it a candidate for food & beverage systems that need to operate in moist environments.

Features

- Temperature switching range from -40°C to 135°C
- Easy to mount clip
- Innovative dry seal
- 100k cycle life
- Automatic reset

Application Examples

- HVAC
- White products
- Refrigerators
- Heat pumps

Agency Approval

- UL/CSA recognized
- ENEC/ENEC recognized



5100 Series

The 5100 Series is a single pole, single throw, snap-action, hermetically sealed thermostat built in a probe package.

Application Opportunities

The 5100 Series' probe design makes it an ideal temperature switch for applications that need switching in an immersion environment. Its construction makes it rugged enough for either high vibration applications or ones under high pressures.

Features

- Stainless steel construction
- Operating temperature of 1.67°C to 249°C
- Hermetic glass seal (isolated-case only)
- Ideal for immersion switching
- Pressure exposure limit of 1500 PSI
- 100k cycle life

Application Examples

- Hydraulic systems
- Degreasers
- Chemical baths
- Oil and transmission protection

Agency Approval

- UL E36687 and E66685
- CSA LR25561-6 and LR25561-8
- Thermal shock specifications per MIL-STD-202, method 107, test condition B



5011 Series

The 5011 Series is a positive snap action, single pole, single throw hermetically sealed thermostat that is built into a case grounded or case isolated package.

Application Opportunities

The 5011 Series is designed as a surface mount thermostat for applications with heavy environmental concerns or applications that require the thermostat to be an isolated device.

Features

- Hermetic glass seal
- Case isolated and case grounded options available
- 100k cycle life
- Operating temperature range from 60°C to 249°C

Application Examples

- Printed circuit board protection
- Air or water cooled engines and transmission

Agency Approval

- RoHS compliant
- Thermal shock specifications per MIL-STD-202, Method 107 Test Condition B



5003 Series

The 5003 Series is a positive snap action, single pole, single throw thermostat built in a low profile package.

Application Opportunities

The 5003 Series is ideal for applications where space is at a premium due to its compact size. The construction of the switch assembly offers excellent shock and vibration resistance and is ideal for high humidity and contaminating atmospheres.

Features

- Low profile design
- 100k cycle life
- Operating temperature range of 1.67°C to 162.78°C

Application Examples

- Power supplies
- Laser systems
- HVAC
- Generators
- Air compressors
- Printing press machines
- Packaging equipment
- Warming plates
- Industrial refrigeration units
- Lighting system amplifiers
- Battery systems

Agency Approval

- RoHS compliant per EU directive 2002/95/EC



Thermal Sensing & Switching Thermostats



Thermal sensing and switching thermostats are small temperature switches designed specifically around placement on pc boards or power supplies. They are built in industry standard packages for easy installation.

6600 Series

The 6600 Series is a positive snap action, single pole, single throw sub-miniature thermostat in a package that dimensionally conforms to standard 8-pin DIP.

Application Opportunities

The 6600 Series is ideal for use on PC boards. Typical uses include turning on an indicator light, sounding an alarm, switching on a control circuit, or even switching a circuit to shut down a system.

Features

- 8-pin DIP international electronic package standard
- Operating temperature of 40°C to 130°C
- 25,000 cycles @ 46 VDC, 1.0A
- 30,000 cycles @ 120 VAC, 1.0A
- 100,000 cycles @ 5 VDC, 0.001A (gold plated contacts)

Application Examples

- Power supplies
- Battery chargers
- Servo systems
- Machine tools
- Datacom equipment

- Emergency lighting
- RF and microwave amplifiers
- Test equipment

Agency Approval

- Vibration specifications per MIL-STD-202, method 204D, test condition D
- Shock specifications per Mil-STD-202, method 213, test condition C
- cRUus recognized E36687
- VDE approval 0631/12.83
- RoHS compliant per EU Directive 2002/95/EC



6700 Series

The 6700 Series is a positive snap action, single pole, single throw sub-miniature thermostat in a package that conforms to standard Y220/TO222, which allows for the sensor to be automatically soldered onto PC boards.



Application Opportunities

The 6700 Series is ideal for PC board and power supply applications that require low space usage. It is suited well for turning on an indicator light, sounding an alarm, switch on a control circuit, or even to switch a circuit to shut down a system.

Features

- Y-220/TO-222 international electronic package standard
- Operating temperature of 40°C to 130°C
- 25,000 cycles @ 46 VDC, 1.0A
- 30,000 cycles @ 120 VAC, 1.0A
- 100,000 cycles @ 5 VDC, 0.001A (gold plated contacts)

Application Examples

- Power supplies
- Battery chargers
- Servo systems
- Machine tools
- Datacom equipment
- Emergency lighting
- RF and microwave amplifiers
- Test equipment

Agency Approval

- Vibration specifications per MIL-STD-202, method 204D, test condition D
- Shock specifications per Mil-STD-202, method 213, test condition C
- cRUus recognized E36687
- VDE approval 0631/12.83
- RoHS compliant per EU Directive 2002/95/EC